

# HANDTMANN COMPONENTS

## VALVES AND FITTINGS FOR HYGIENIC PROCESSES

Technical Overview



Contact us:  
[sales.fittings@handtmann.de](mailto:sales.fittings@handtmann.de)



### TANK DOME CAP



- DN 450-800
- Standard & customized

### TANK DOME FITTINGS



- DN 25-200
- Standard & customized

### SAFETY VALVES



- Spring loaded: DN 15-80 (ASME available)
- Weight loaded: DN 65-125

### VACUUM VALVES



- Spring loaded: DN 25-80
- Weight loaded: DN 25-400

### BUTTERFLY VALVES



- DN 25-200
- Manual or with pneumatic actuator

### BUNGING VALES, OVERFLOW- / PRESSURE RETENTION VALVES



- Bunging device: DN 15-40
- Overflow- /pressure retention valve: DN 15-80

### DOUBLE SEAT VALVES



- DN 50-200
- Double Balancer
- Single seat lifting

#### GENERAL EXECUTION:

Materials: 1.4301, 1.4307, 1.4404

From 0-90°C, + 140°C short term

Sealing materials: EPDM (other materials on request)

Surface roughness of media touched parts: Ra ≤ 0,8 µm (other surface qualities on request)

ISO 9001 & EHEDG design

